

**405.1687****INTERLOCKED SOCKET**

16A 3P+N+E 6h 346-415V 60Hz 50Hz  
136X125MM Screw terminals With  
mechanical interlock



EN 60309-1/A1 (2007)  
EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-1/A2 (2012)  
EN 60309-2/A1 (2007)  
EN 60309-2/A2 (2012)  
EN 60309-4 (2007)  
EN 60309-4/A1 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OMNIA Series

Synthetical description

INTERLOCKED SOCKET

Mounting version

FLUSH MOUNTING

### ■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

### ■ PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)

### ■ DIMENSIONAL CHARACTERISTICS

Flange	136X125MM
--------	-----------

### ■ DOWNLOAD

Technical drawing [PDF]  
Technical drawing [DWG]  
Technical drawing [STP]  
Instruction manual

### ■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER